



CERTIFICATE OF CALIBRATION

Model: 4040

This is to certify that all the products distributed by Rubbermaid Commercial Products are calibrated at the time of manufacturing to tolerances in the specification. This does not certify that the products have not been altered by tampering or damaged by misuse or mishandling. This is not meant to supersede individual or internal calibration programs.

Section 1: Calibration Method

Model 4040 is calibrated to exact specification during manufacture in China.

Section 2: Calibration Procedure

Calibration procedure may only be performed by approved operators. Rubbermaid manufacturing procedures require verification of conformance to product specifications by production personnel at the time of manufacture. Product release is contingent on acceptance by Inspection personnel according to Procedure 10-4-01 and is based on sampling plan ANSI/ASQC Standard Z1.4-1993

Section 3: Performance Criteria for 400 lb. Capacity

1% of applied weight at 25° C 10° C to 20° C with less than .05% error

Checkpoint	Tolerance
50 lb.	+/- 0.5 lb.
100 lb.	+/- 1 lb.
200 lb.	+/- 1 lb.
300 lb.	+/- 1 lb.
400 lb.	+/- 1 lb.

Section 4: Environmental Conditions During Testing

Ambient temperature of 77° F ; Relative humidity of 65%

Section 5: Pertinent Information

Weights used for the calibration /verification procedure are certified to tolerances found in

Rubbermaid Commercial Products, LLC Newell Rubbermaid Company
8900 NorthPointe Executive Drive,
Huntersville, NC 28078

Christian Zhao, Senior quality manager
Signature

Jul 20, 2021
Date

This document cannot be reproduced without the written consent of Rubbermaid Inc.

