

# SEMI-AUTOMATIC STRETCH WRAP MACHINE

**ULINE** H-1020

1-800-295-5510 [uline.com](http://uline.com)

## SYSTEM SPECIFICATIONS

### PRODUCTION CAPACITY

- 10-20 Loads Per Hour
- 52 x 52 x 80"

### TURNTABLE SPECIFICATIONS

- 3.1" Floor-To-Table Height
- 60" Diameter Turntable
- Baldor 90V DC Turntable Drive
- V-Belt Table Drive
- Adjustable Turntable Speed 0-12 rpm

### FILM DELIVERY SYSTEM

- Simplified Stretch 60% to 150%
- 10" Diameter Roll Capacity
- 20" Roll Width Capacity

### OPERATING CONTROLS

- Adjustable Top and Bottom Wrap Counts
- Push/Pull Red E-Stop Button
- Green Start Push Button
- Carriage Spiral Speed Dial
- Carriage Jog UP/DOWN Button
- Carriage Pause (Banding) Button
- Turntable Speed Dial
- System Reset Button
- Turntable Jog Button
- Main Power ON/OFF Switch
- Wrap Mode Selector: Allows operator to wrap up only, up and down, or reset to home location

### ELECTRICAL

- 115V 15AMP Electrical Input
- JIC Standard
- Photo Eye: Senses load height
- Baldor 90V DC TEFC Motors

### SAFETY FEATURES THAT SHUT OFF POWER

- Opening Control Panel Door
- Safety Bar: Underneath carriage

### LOAD CAPACITIES

- 4,000 lb. Capacity
- 1-12 rpm

### FILM ELEVATOR

- Chain Carriage Lift
- Variable UP/DOWN Speed
- Baldor 90V DC Elevator Drive
- Photo Eye Height Sensor
- 2 Selectable wrap modes:
  - a. Wrap Up and Wrap Down
  - b. Wrap Up and Stops. Push START Button; carriage automatically returns

The information contained herein was prepared by the manufacturer and is provided as a service to our customers. Uline is not responsible for the accuracy or completeness of this information.