# Floor Science®

### Floor Science®

#### **Easy Apply High Gloss Floor Finish**

Floor Science® Easy Apply High Gloss Floor Finish is an easy-to-apply floor finish/sealer that is formulated to work with any maintenance method and equipment. Use the complete Floor Science system to create and maintain a consistently brilliant shine on floors with minimal time and effort.

#### Features & Benefits

- Simplifies floor care program
- Synthetic polymeric floor finish creates initial high-gloss without buffing or burnishing
- Minimizes the tendency to show scuffs and black heel marks. Features outstanding leveling and adhesion properties
- Solids Content 20%
- Meets ASTM D-2047 slip resistance requirements
- One gallon covers up to 2,500 sq. ft. (232 sq. m)

#### **Applications**

- The "built-in" sealer means the finish acts as its own sealer—no separate product required
- Works on nearly all types of floors and responds beautifully to conventional, high-speed or UHS equipment and maintenance procedures
- Works with non-buff, dry buff and spray buff programs. Responds to 175 through 2000 equipment





## Floor Science®

#### Floor Science®

#### **Easy Apply High Gloss Floor Finish**

#### **Use instructions**

Blockade areas to be stripped or finished. Floors will be very slippery until dry.

- 1. Strip floor, using Floor Science® Heavy Duty Floor Stripper per the label instructions.
- 2. Apply 2-3 uniform coats using a clean mop
- 3. Allow 40 minutes drying time between coats.

#### **RECOAT**

- 1. Dust mop or sweep
- 2. Clean floor with a mop or an automatic scrubber using the recommended Floor Science® Neutral Floor Cleaner according to label directions
- 3. Blockade area and apply 1-2 uniform coats of finish using a clean mop.

#### **MAINTENANCE**

- 1. Dust mop or sweep.
- 2. Clean the floor With a mop or an automatic scrubber using the recommended Floor Science® cleaner according to label directions
- 3. To enhance appearance, use any of the following methods: Spray buff with Floor Science® Cleaner & Restorer Spray Buff, a red pad and 175-1500 rpm equipment. Dry buff using a medium to aggressive pad and 1000-1500 rpm equipment. Ultra High Speed burnish using a medium to aggressive pad and 2000 rpm equipment

#### **REMOVAL**

1. Remove using Floor Science® Heavy Duty Floor Stripper according to label directions

Technical data	Floor Science® Easy Apply High Gloss Floor Finish
Color/Form	Off-White
рН	8.8
Scent	Ammonia
Shelf Life	2 years

Product	Pack size	Dilution	Product code	
Floor Science® Easy Apply High Gloss Floor Finish	4 x 1 gal. / 3.78 L Containers	Ready to Use	CBD540410	*
Floor Science® Easy Apply High Gloss Floor Finish	1 x 5 gal./18.9 L Envirobox <sup>TM/MC</sup>	Ready to Use	CBD540427	+

#### Safe handling

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use; and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDS are available online at www.diversey.com or by calling 888.352.2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate.