

MA 4522 Red

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Revision Date: 3/13/2018

Date of issue: 11/30/2015

Version: 1.0

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: MA 4522 Red

Product Code: S-12700, S-12699

Intended Use of the Product

Use of the Substance/Mixture: Industrial marking on wood, metal, glass, concrete.

Name, Address, and Telephone of the Distributor

Uline Inc

12575 Uline Drive

Pleasant Prairie, WI 53158

Tel: 1-800-295-5510

Emergency Telephone Number

CHEMTREC- US/Canada: 1-800-424-9300

International: +1-703-3887

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS-US classification

Flam. Liq. 3 H226

Eye Dam. 1 H318

STOT SE 3 H336

Full text of H-phrases: see section 16

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H226 - Flammable liquid and vapor.
H318 - Causes serious eye damage.
H336 - May cause drowsiness or dizziness.

Precautionary Statements (GHS-US)

: P210 - Keep away from extremely high or low temperatures, ignition sources, and incompatible materials. - No smoking.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical, ventilating, and lighting equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P261 - Avoid breathing vapors, mist, or spray.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves, protective clothing, and eye protection.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a poison center or doctor.
P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.

MA 4522 Red

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial and international regulations.

P403+P233+P235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

| Name | Product Identifier | % (w/w) | GHS-US classification |
|-----------------------------------|--------------------|---------------------|---|
| Propylene glycol monomethyl ether | (CAS No) 107-98-2 | 25 - 30, 30 - 50 | Flam. Liq. 3, H226 STOT SE 3, H336 |
| n-Propanol | (CAS No) 71-23-8 | 25 - 30, 30 - 50 | Flam. Liq. 2, H225 Eye Dam. 1, H318 STOT SE 3, H336 |

Full text of H-phrases: see section 16

*The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200].

**A range of concentration as prescribed by Controlled Products Regulations has been used where necessary, due to varying composition.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

Most Important Symptoms and Effects Both Acute and Delayed

General: May cause drowsiness and dizziness. Causes serious eye damage.

Inhalation: High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

Skin Contact: Prolonged exposure may cause skin irritation.

Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva.

Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: Not available

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂). Water may be ineffective but water should be used to keep fire-exposed container cool.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable liquid and vapor.

Explosion Hazard: May form flammable or explosive vapor-air mixture.

MA 4522 Red

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂).

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges. Do not breathe vapor, mist or spray.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Eliminate ignition sources.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools.

Reference to Other Sections

See Heading 8. Exposure controls and personal protection. See Section 13, Disposal Considerations.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid breathing vapors, mist, spray. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid contact with eyes, skin and clothing. Do not get in eyes, on skin, or on clothing.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

Storage Conditions: Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

Specific End Use(s)

Use of the Substance/Mixture: Industrial marking on wood, metal, glass, concrete.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

MA 4522 Red

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

| | | |
|---|---------------------------------------|--|
| Propylene glycol monomethyl ether (107-98-2) | | |
| USA ACGIH | ACGIH TWA (ppm) | 50 ppm |
| USA ACGIH | ACGIH STEL (ppm) | 100 ppm |
| USA ACGIH | ACGIH chemical category | Not Classifiable as a Human Carcinogen |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 360 mg/m ³ |
| USA NIOSH | NIOSH REL (TWA) (ppm) | 100 ppm |
| USA NIOSH | NIOSH REL (STEL) (mg/m ³) | 540 mg/m ³ |
| USA NIOSH | NIOSH REL (STEL) (ppm) | 150 ppm |
| Alberta | OEL STEL (mg/m ³) | 553 mg/m ³ |
| Alberta | OEL STEL (ppm) | 150 ppm |
| Alberta | OEL TWA (mg/m ³) | 369 mg/m ³ |
| Alberta | OEL TWA (ppm) | 100 ppm |
| British Columbia | OEL STEL (ppm) | 75 ppm |
| British Columbia | OEL TWA (ppm) | 50 ppm |
| Manitoba | OEL STEL (ppm) | 100 ppm |
| Manitoba | OEL TWA (ppm) | 50 ppm |
| New Brunswick | OEL STEL (mg/m ³) | 553 mg/m ³ |
| New Brunswick | OEL STEL (ppm) | 150 ppm |
| New Brunswick | OEL TWA (mg/m ³) | 369 mg/m ³ |
| New Brunswick | OEL TWA (ppm) | 100 ppm |
| Newfoundland & Labrador | OEL STEL (ppm) | 100 ppm |
| Newfoundland & Labrador | OEL TWA (ppm) | 50 ppm |
| Nova Scotia | OEL STEL (ppm) | 100 ppm |
| Nova Scotia | OEL TWA (ppm) | 50 ppm |
| Nunavut | OEL STEL (mg/m ³) | 540 mg/m ³ |
| Nunavut | OEL STEL (ppm) | 150 ppm |
| Nunavut | OEL TWA (mg/m ³) | 360 mg/m ³ |
| Nunavut | OEL TWA (ppm) | 100 ppm |
| Northwest Territories | OEL STEL (ppm) | 150 ppm |
| Northwest Territories | OEL TWA (ppm) | 100 ppm |
| Ontario | OEL STEL (ppm) | 100 ppm |
| Ontario | OEL TWA (ppm) | 50 ppm |
| Prince Edward Island | OEL STEL (ppm) | 100 ppm |
| Prince Edward Island | OEL TWA (ppm) | 50 ppm |
| Québec | VECD (mg/m ³) | 553 mg/m ³ |
| Québec | VECD (ppm) | 150 ppm |
| Québec | VEMP (mg/m ³) | 369 mg/m ³ |
| Québec | VEMP (ppm) | 100 ppm |
| Saskatchewan | OEL STEL (ppm) | 150 ppm |
| Saskatchewan | OEL TWA (ppm) | 100 ppm |
| Yukon | OEL STEL (mg/m ³) | 450 mg/m ³ |
| Yukon | OEL STEL (ppm) | 150 ppm |
| Yukon | OEL TWA (mg/m ³) | 360 mg/m ³ |
| Yukon | OEL TWA (ppm) | 100 ppm |
| n-Propanol (71-23-8) | | |
| USA ACGIH | ACGIH TWA (ppm) | 100 ppm |
| USA ACGIH | ACGIH chemical category | Not Classifiable as a Human Carcinogen |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 500 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 200 ppm |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 500 mg/m ³ |
| USA NIOSH | NIOSH REL (TWA) (ppm) | 200 ppm |

MA 4522 Red

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

| | | |
|-------------------------|---------------------------------------|-----------------------|
| USA NIOSH | NIOSH REL (STEL) (mg/m ³) | 625 mg/m ³ |
| USA NIOSH | NIOSH REL (STEL) (ppm) | 250 ppm |
| USA IDLH | US IDLH (ppm) | 800 ppm |
| Alberta | OEL STEL (mg/m ³) | 984 mg/m ³ |
| Alberta | OEL STEL (ppm) | 400 ppm |
| Alberta | OEL TWA (mg/m ³) | 492 mg/m ³ |
| Alberta | OEL TWA (ppm) | 200 ppm |
| British Columbia | OEL TWA (ppm) | 100 ppm |
| Manitoba | OEL TWA (ppm) | 100 ppm |
| New Brunswick | OEL STEL (mg/m ³) | 614 mg/m ³ |
| New Brunswick | OEL STEL (ppm) | 250 ppm |
| New Brunswick | OEL TWA (mg/m ³) | 492 mg/m ³ |
| New Brunswick | OEL TWA (ppm) | 200 ppm |
| Newfoundland & Labrador | OEL TWA (ppm) | 100 ppm |
| Nova Scotia | OEL TWA (ppm) | 100 ppm |
| Nunavut | OEL STEL (mg/m ³) | 615 mg/m ³ |
| Nunavut | OEL STEL (ppm) | 250 ppm |
| Nunavut | OEL TWA (mg/m ³) | 491 mg/m ³ |
| Nunavut | OEL TWA (ppm) | 200 ppm |
| Northwest Territories | OEL STEL (ppm) | 400 ppm |
| Northwest Territories | OEL TWA (ppm) | 200 ppm |
| Ontario | OEL TWA (ppm) | 100 ppm |
| Prince Edward Island | OEL TWA (ppm) | 100 ppm |
| Québec | VECD (mg/m ³) | 614 mg/m ³ |
| Québec | VECD (ppm) | 250 ppm |
| Québec | VEMP (mg/m ³) | 492 mg/m ³ |
| Québec | VEMP (ppm) | 200 ppm |
| Saskatchewan | OEL STEL (ppm) | 400 ppm |
| Saskatchewan | OEL TWA (ppm) | 200 ppm |
| Yukon | OEL STEL (mg/m ³) | 625 mg/m ³ |
| Yukon | OEL STEL (ppm) | 250 ppm |
| Yukon | OEL TWA (mg/m ³) | 500 mg/m ³ |
| Yukon | OEL TWA (ppm) | 200 ppm |

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection. Face shield.



Materials for Protective Clothing: Chemically resistant materials and fabrics. Wear fire/flammable resistant/retardant clothing.

Hand Protection: Wear protective gloves.

Eye Protection: Chemical goggles or face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

MA 4522 Red

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

| | |
|---|---|
| Physical State | : Liquid |
| Appearance | : According to product specification |
| Odor | : Alcohol-like |
| Odor Threshold | : Not available |
| pH | : Not available |
| Evaporation Rate | : Not available |
| Melting Point | : Not available |
| Freezing Point | : Not available |
| Boiling Point | : 96 °C (204.8 °F) |
| Flash Point | : 23 °C (73.4 °F) |
| Auto-ignition Temperature | : 287 °C (548.6 °F) |
| Decomposition Temperature | : Not available |
| Flammability (solid, gas) | : Not available |
| Lower Flammable Limit | : Not available |
| Upper Flammable Limit | : Not available |
| Vapor Pressure | : 19 hPa |
| Relative Vapor Density at 20 °C | : Not available |
| Relative Density | : Not available |
| Specific gravity / density | : 0.83 g/cm ³ |
| Specific Gravity | : Not available |
| Solubility | : Water: Fully miscible |
| Partition Coefficient: N-Octanol/Water | : Not available |
| Viscosity | : Not available |
| Viscosity, Dynamic | : 4 mPa.s at 20 °C |
| Explosion Data – Sensitivity to Mechanical Impact | : Not expected to present an explosion hazard due to mechanical impact. |
| Explosion Data – Sensitivity to Static Discharge | : Static discharge could act as an ignition source. |

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion.

Chemical Stability: Flammable liquid and vapor. May form flammable or explosive vapor-air mixture.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Causes serious eye damage.

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

MA 4522 Red

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Specific Target Organ Toxicity (Single Exposure): May cause drowsiness or dizziness.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

| Propylene glycol monomethyl ether (107-98-2) | |
|--|----------------|
| LD50 Oral Rat | 5000 mg/kg |
| LD50 Dermal Rabbit | 13 g/kg |
| LC50 Inhalation Rat | > 6 mg/l/4h |
| LC50 Inhalation Rat | 27.3 mg/l/4h |
| n-Propanol (71-23-8) | |
| LD50 Dermal Rabbit | 4049 mg/kg |
| LC50 Inhalation Rat | > 13548 ppm/4h |

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Not classified.

| Propylene glycol monomethyl ether (107-98-2) | |
|--|---|
| LC50 Fish 1 | 20.8 g/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| EC50 Daphnia 1 | 23300 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| n-Propanol (71-23-8) | |
| LC50 Fish 1 | 4480 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| EC50 Daphnia 1 | 3642 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| EC50 Daphnia 2 | 3339 - 3977 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |

Persistence and Degradability

| MA 4522 Red | |
|-------------------------------|------------------|
| Persistence and Degradability | Not established. |

Bioaccumulative Potential

| MA 4522 Red | |
|--|------------------|
| Bioaccumulative Potential | Not established. |
| Propylene glycol monomethyl ether (107-98-2) | |
| BCF Fish 1 | < 2 |
| Log Pow | -0.437 |
| n-Propanol (71-23-8) | |
| Log Pow | 0.25 - 0.34 |

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations

Additional Information: Handle empty containers with care because residual vapors are flammable.

Ecology – Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

In Accordance with DOT

Proper Shipping Name : ALCOHOLS, N.O.S.(n-Propanol and Propylene glycol monomethyl ether)

MA 4522 Red

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Hazard Class : 3
Identification Number : UN1987
Label Codes : 3
Packing Group : III



In Accordance with IMDG

Proper Shipping Name : ALCOHOLS, N.O.S. (n-Propanol and Propylene glycol monomethyl ether)
Hazard Class : 3
Identification Number : UN1987
Packing Group : III
Label Codes : 3
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-D



In Accordance with IATA

Proper Shipping Name : ALCOHOLS, N.O.S. (n-Propanol and Propylene glycol monomethyl ether)
Packing Group : III
Identification Number : UN1987
Hazard Class : 3
Label Codes : 3
ERG Code (IATA) : 3L



In Accordance with TDG

Proper Shipping Name : ALCOHOLS, N.O.S. (n-Propanol and Propylene glycol monomethyl ether)
Packing Group : III
Hazard Class : 3
Identification Number : UN1987
Label Codes : 3



SECTION 15: REGULATORY INFORMATION

US Federal Regulations

| | |
|---|--|
| MA 4522 Red | |
| SARA Section 311/312 Hazard Classes | Fire hazard Immediate (acute) health hazard |
| Propylene glycol monomethyl ether (107-98-2) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| n-Propanol (71-23-8) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

US State Regulations

| | |
|--|--|
| Propylene glycol monomethyl ether (107-98-2) | |
| U.S. - Massachusetts - Right To Know List | |
| U.S. - New Jersey - Right to Know Hazardous Substance List | |
| U.S. - Pennsylvania - RTK (Right to Know) List | |
| n-Propanol (71-23-8) | |
| U.S. - Massachusetts - Right To Know List | |
| U.S. - New Jersey - Right to Know Hazardous Substance List | |
| U.S. - Pennsylvania - RTK (Right to Know) List | |

Canadian Regulations

| | |
|-----------------------------|--|
| MA 4522 Red | |
| WHMIS Classification | Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects |

MA 4522 Red

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations



Propylene glycol monomethyl ether (107-98-2)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification

Class B Division 2 - Flammable Liquid

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

n-Propanol (71-23-8)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification

Class B Division 2 - Flammable Liquid

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 03/13/2018

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

| | |
|--------------|---|
| Eye Dam. 1 | Serious eye damage/eye irritation Category 1 |
| Flam. Liq. 2 | Flammable liquids Category 2 |
| Flam. Liq. 3 | Flammable liquids Category 3 |
| STOT SE 3 | Specific target organ toxicity (single exposure) Category 3 |
| H225 | Highly flammable liquid and vapor |
| H226 | Flammable liquid and vapor |
| H318 | Causes serious eye damage |
| H336 | May cause drowsiness or dizziness |

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS